

Accautotool

Auto Code Co.,Ltd.

TLT240SB----Standard Floorplate Two Post Lift

[Call for Pricing](#)

Functions and Features

The cable and oil pipe are fully concealed, with decent and elegant appearance.

Designed based on the international standard, meeting the demand of the garage and workshop.

Top limit switch, effectively protecting the vehicle from overhead collision.

Dual hydraulic cylinders drive, stable lifting and lowering.

Electromagnetic full-scope safety lock.

Lowering electrically, safe and simple in operation.

Adopt two steel cables for equalization, force two carriages to move synchronously, and effectively prevent the vehicle from tilting.

Lowest height of lifting pad is 110mm, good for repairing low chassis or low profile car.

Technical Specifications

Capacity 4 TON (9000 lbs)

Lifting height 1950 mm (76.8inch)

Lifting time 50 Sec

Lowering time 40 Sec

Motor power 2.2 kw

Passing width 2486 mm (97.9 inch)

Overall width 3370 mm (132.7 inch)

Overall height 2860 mm (112.6 inch)

Noise:

Working noise: ≤ 80 dB(A)

Power unit:

Working pressure: 16MPa (TLT235SBA)

18MPa (TLT240SBA)

Electrical parameters of the machine:

Motor:

Three phase: 230V/60Hz 2.2kw; 380V/50Hz 2.2kw

Single phase: 110V/60Hz 2.2kw; 220V/60Hz 2.2kw

220V/50Hz 2.2kw

∧ ∧

Environmental Requirement

Working temperature: $-5^{\circ}\text{C} \sim +40^{\circ}\text{C}$

Transport/storage temperature: $-5^{\circ}\text{C} \sim +40^{\circ}\text{C}$

Relative humidity: Temperature $+30^{\circ}\text{C}$, relative humidity 80%

Height above sea level: No more than 2000m

[Vendor Information](#)